

### **BLANK PAGE**



IS 11644: 1999

## भारतीय मानक वायुआकाशीय काबले और पेंच बनाने और स्थिति की छूटें (पहला पुनरीक्षण)

# Indian Standard TOLERANCES OF FORM AND POSITION FOR AEROSPACE BOLTS AND SCREWS

(First Revision)

ICS 49.030.20

© BIS 1999

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

### **FOREWORD**

This Indian Standard (First Revision) was adopted by the Bureau of Indian Standards, after the draft finalized by the Aircraft and Space Vehicles Sectional Committee had been approved by the Transport Engineering Division Council.

This Indian Standard was published in 1986. The revision of this standard has been made to bring it inline with ISO 7913: 1994 'Aerospace — Bolts and screws, metric — Tolerances of form and position', issued by the International Organization for Standardization (ISO).

The committee responsible for preparation of this standard is given in Annex A.

For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS 2: 1960 'Rules for rounding off numerical values (revised)'. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

### Indian Standard

# TOLERANCES OF FORM AND POSITION FOR AEROSPACE BOLTS AND SCREWS

(First Revision)

### 1 SCOPE

This Indian Standard specifies the tolerances of form and position applicable to all types of metric bolts and screws in nominal diameter range 3 to 24 mm used in aerospace construction.

### **2 REFERENCES**

2.1 The following standards contain provisions which through reference in this text, constitute provision of this standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below:

IS No. Title

8000 Geometrical tolerancing on technical

drawings:

(Part 1): 1985 Tolerances of form orientation,

location and run-out and appropriate geometrical definitions (first

revision)

(Part 2): 1992 Maximum material principles (first

revision)

### **3 CHARACTERISTICS**


The description of characteristics for various types of bolts and screws shall conform to Table 1. The tolerances of form and position shall be as given in the illustrations in the table. All tolerance, descriptions and illustrations conform to IS 8000 (Part 1) and IS 8000 (Part 2). All tolerance values have been expressed in millimetres.

Table 1 Description and Illustration of Bolts and Screws

(Clause 3)

# SI No. Description 3.1 Perpendicularity of bolt underhead bearing surface 1 0.08 A

3.2 Straightness of total bolt shank length



3.3 Run-out of the external flange diameter of bihexagonal and spline head bolts




Table 1 (Continued)

SI No. Description Illustration 3.4 Run-out of the external wrenching diameter of bihexagonal Α and spline head bolts XXA 3.5 Run-out of the width across corners of hexagonal head bolts Position of split pin hole in bolt thread В **♦ • 0.4 M** B A M

Table 1 (Continued)

SI No. Description Illustration 3.7 Run-out of the conical or cylindrical portion of pan head bolts φD 0.4 M B A M 3.8 Position of locking wire hole in hexagonal, bihexagonal and spline head bolts **♦** • 0.4 **M** B A **M** 0.4 M B A M 3.9 Run-out of the conical portion of countersunk head bolts 0.08

Table 1 (Concluded)

SI No.	Description	Illustration
3.10	Perpendicularity and concavity at the top of countersunk head bolts	1 0.08 A NOT CONCAVE

- \*For bolts and screws with unthreaded shank length:
- a) ≥D, Datum A is the unthreaded shank and can be located anywhere within a maximum length equal to drameter D from the head shank intersection.
- b) < D or threaded to head: Datum A is the pitch diameter and can be located anywhere within a maximum length equal to diameter D nearest the head-shank intersection.

where

- D = nominal thread diameter.
- M = based on maximum material principle, for details, see IS 8000 (Part 2).

### **4 DIMENSIONAL TOLERANCES**

Dimensional tolerances shall conform to Table 2 for nominal thread diameter from 3 to 24 mm. All tolerance values are expressed in millimetres.

Table 2 Dimensional Tolerances Values

Nominal Thread Diameter	V**		X	Y	Z
	Short and Medium Length Thread	Long Length Thread and Threaded to the Head			
3		0.003	0.08	0.15	0.11
3.5			0.09	0.18	0.12
4	]		0.1	0.2	0.14
5	0.002		0.13	0.25	0.18
6			0.15	0.3	0.21
7			0.18	0.35	0.25
-8			0.2	0.4	0.28
10		0.002 5	0.25	0.5	0.35
12			0.3	0.6	0.45
14	7		0.35	0.7	0.49
16	0.001 5		0.4		0.56
18			0.45		0.63
20			0.5	0.75	0.7
22	0.001	0.002	0.55		0.75
24	0.001		0.6		0.75

<sup>\*</sup>Parameter 'V' is dimensionsless (millimetre per millimetre).

### ANNEX A

### (Foreword)

### **COMMITTEE COMPOSITION**

Aircraft and Space Vehicles Sectional Committee, TED 14

Chairman

SHRI M. V. SUNDARAM

Members

Shri R. N. Sharma (Alternate to Shri M. V. Sundaram)

**Shri B. K. J**oshi

SHRI N. S. MUNDEY (Alternate)

SHRI RAMAN CHOPRA
PROF T. S. RAMAMURTHY
DR V. S. HOLLA (Alternate)

SHRI J. P. SINGH

DRT. S. BALASUBRAMANIUM (Alternate)

Shri A. Venkoba Rao Shri Perduman Singh

SHRI V. K. KALYANAM (Alternate)

SHRI S. GOVINDARAJAN

SHRI R. N. DESAI (Alternate)

SHRI VIJAI KUMAR

SHRI S. V. SHARMA (Alternate)

SHRI S. K. VELUSWAMY

SHRI S. RAMAKRISHNAN (Alternate)

SHRI W. G. NAFDE SHRI S. K. CHAKRAVARTI

Shri S. Chatterjee (*Alternate*) Shri K. S. Venkataraman Shri Milan Kumar Basu

Shri D. R. Arora (Alternate)

SHRI S. C. SHRIMALI SHRI A. R. GULATI,

Director (Transport Engineering)

Representing

Department of General of Aeronautical Quality Assurance (DGAQA), New Delhi

Directorate General of Civil Aviation, New Delhi

Indian Airlines, New Delhi

Indian Institute of Science, Bangalore

National Aeronautical Laboratory (CSIR), Bangalore

Hindustan Aeronautic Ltd (Aircraft Design Bureau), Bangalore

Centre for Military Airworthiness and Certification (CEMILAC), Bangalore

Bharat Dynamics Ltd, Hyderabad

Vikram Sarabhai Space Centre, Trivandrum

Hindustan Aeronautic Ltd, Bangalore

Gas Turbine Research Establishment, Bangalore

Dunlop India Ltd (R & D), Mumbai

Ministry of Defence (DRDL), Hyderabad Hindustan Aeronautics Ltd, Lucknow

Aeronautical Development Agency (ADA), Bangalore

Director General, BIS (Ex-officio Member)

Member Secretary Shri P. P. Singh

Joint Director (Transport Engineering), BIS

Accessories, Fittings and Fasteners for Aircraft and Space Vehicles Subcommittee, TED 14:2

Convener

SHRI A. VENKOBA RAO

Hindustan Aeronautics Ltd (Aircraft Design Bureau), Bangalore

Members

Shri D. Krishna Rao (Alternate to

Shri A. Venkoba Rao)

SHRI S. B. PRASAD

SHRI K. N. SINHA (Alternate) SHRI N. M. WALECHA

SHRI S. M. BAWA SHRI S. RAGHAVA

SHRI G. KOTHANDARAMAN (Alternate)

Dr K. Abraham Jacob Shri P. V. Deshmukh

SHRI K. A. PAUL (Alternate)

DR M. R. MADHAVA SHRI S. VEERARAGHAVAN SHRI S. GOVINDARAJAN

SHRI R. N. DESAI (Alternate)

SHRI S. C. SHRIMALI SHRI VINOD SAXENA Directorate General of Aeronautical Quality Assurance (DGAOA), New Delhi

Directorate General of Civil Aviation, New Delhi

Indian Airlines, New Delhi

Vikram Sarabhai Space Centre, Trivandrum

Aeronautical Development Establishment, Ministry of Defence (R&D), Bangalore

Hindustan Aeronautics Ltd, Nasik

National Aerospace Laboratories, Bangalore Bashi Aerospace Pvt Ltd, Bangalore Bharat Dynamics Ltd, Hyderabad

Aeronautical Development Agency (ADA), Bangalore

Hindustan-Aeronautics Ltd, Lucknow

### **Bureau of Indian Standards**

BIS is a statutory institution established under the *Bureau of Indian Standards Act*, 1986 to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

### Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

### **Review of Indian Standards**

Amend No.

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the latest issue of 'BIS Catalogue' and 'Standards: Monthly Additions'.

This Indian Standard has been developed from Doc: No. TED 14 (168).

### Amendments Issued Since Publication

Date of Issue

	The state of the s				
	BUREAU OF INDIAN STANDARDS				
<b>Head</b> quart	ers:				
	avan, 9 Bahadur Shah Zafar Marg, New Delhi 110 002 s: 323 01 31, 323 33 75, 323 94 02	Telegrams: Manaksanstha (Common to all offices)			
Regional (	Offices:	Telephone			
Central	: Manak Bhavan, 9 Bahadur Shah Zafar Marg NEW DELHI 110 002	$\begin{cases} 323 & 76 & 17 \\ 323 & 38 & 41 \end{cases}$			
Eastern	: 1/14 C. I. T. Scheme VII M, V. I. P. Road, Kankurgachi CALCUTTA 700 054	\[ \begin{cases} 337 84 99, 337 85 61 \\ 337 86 26, 337 91 20 \end{cases} \]			
Northern	: SCO 335-336, Sector 34-A, CHANDIGARH 160 022	$ \begin{cases} 60 38 43 \\ 60 20 25 \end{cases} $			
Southern	: C. I. T. Campus, IV Cross Road, CHENNAI 600 113	$\begin{cases} 235 \ 02 \ 16, 235 \ 04 \ 42 \\ 235 \ 15 \ 19, 235 \ 23 \ 15 \end{cases}$			
Western	: Manakalaya, E9 MIDC, Marol, Andheri (East) MUMBAI 400 093	\begin{cases} 832 92 95, 832 78 58 \\ 832 78 91, 832 78 92 \end{cases}			
Branches	Branches: AHMADABAD. BANGALORE. BHOPAL. BHUBANESHWAR. COIMBATORE. FARIDABAD. GHAZIABAD. GUWAHATI. HYDERABAD. JAIPUR. KANPUR.				

LUCKNOW. NAGPUR. PATNA. PUNE. RAJKOT. THIRUVANANTHAPURAM.

Text Affected